



Photo non  
contractuelle

# AddBike

## Functional check before your first ride

### U-Cargo


NOVEMBER 2023


*This document outlines the correct practices to be followed when using your U-Cargo for the first time.  
It is imperative that you read this entire document before using your U-Cargo for the first time.*

# Hold tight!

Just a few important checks and you can ride your new U-Cargo

To ensure that your product has not been damaged during delivery, here are a few things you should double-check.

- Verify that the motor and the Head/Tail lights are working properly
- Verify that the battery is inserted correctly, press and hold the start button on the display, it should light up blue
- To check that the lights are working, press and hold the button. 

 Start-up (button at the back of the display)



Trigger

Lights activation

- Check the tightness of the wheels with a 15mm spanner. For the Family version, the rear wheel nuts are located under the wooden step frame.



- Then check the **tightness of the handlebar to the stem**. Fasten the front brake and swing the bike back and forth. The handlebars must not move. If it moves, tighten the 4 screws that hold the handlebars to the stem. If you still feel some movement in the head tube, tighten screw A (see figure below). If in doubt, contact your bicycle dealer.
- Then **lock the front wheel by turning the handlebar**. If the handlebar turns but the front wheel does not, the bolts B must be tightened (see figure below).

- **Check your tyre pressure**. It should be between 3.0 and 4.0 bar. If you plan to drive with a load, you should pump your tyres to 4.0 bar.
- **Check the tightening of the saddle**. The saddle should be straight and in line with the bike. If it moves, open the saddle clamp and retighten the knob.



**Have fun with your U-Cargo!**